

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
12 September 2002 (12.09.2002)

PCT

(10) International Publication Number  
**WO 02/071780 A2**

(51) International Patent Classification<sup>7</sup>: **H04Q 7/34**

(21) International Application Number: PCT/US02/06909

(22) International Filing Date: 4 March 2002 (04.03.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/273,739 6 March 2001 (06.03.2001) US

(71) Applicant (for all designated States except US): **AT & T WIRELESS SERVICES, INC.** [US/US]; 14520 N.E. 87th Street, Redmond, WA 98052 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **ZAPPALA, Charles, S.** [US/US]; 16203 NE 3rd Street, Bellevue, WA 98008 (US).

(74) Agents: **COURTNEY, Barbara, B.** et al.; Perkins Coie LLP, P.O. Box 2168, Menlo Park, CA 94026 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: **REAL-TIME NETWORK ANALYSIS AND PERFORMANCE MANAGEMENT**



(57) Abstract: Disclosed embodiments include a method for analyzing the performance of wireless communications network and adjusting parameters in the wireless communications network. In one embodiment, the specific location of a mobile unit is linked with performance data obtained from the mobile unit. In another embodiment, specific mobile units are queried, by, e.g. a network switch, to provide specific performance data. The mobile units respond by sending the performance data and location data to the switch. The performance data and location data are linked. The linked performance data and location data are processed and analyzed to give an accurate representation of network performance from the subscriber's point of view. In one embodiment, E911 technology is used to provide location data.

WO 02/071780 A2



*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**REAL-TIME NETWORK ANALYSIS AND PERFORMANCE MANAGEMENT****BACKGROUND**

[0001] The disclosed embodiments relate to analyzing the performance of a wireless communications network and adjusting parameters in the wireless communications network. Wireless communications systems using cellular or Personal Communication Services (PCS) devices vary in performance from the point of view of the device user. For example, a cellular phone user may experience very good call quality or less than satisfactory call quality depending upon location and/or time of day. Entities that design, construct, and maintain wireless communications networks are very motivated to provide the best service to as many users as possible all of the time. This can be difficult due to the nature of the networks. For example, there is a finite number of physical network components, such as cell sites, PCS sites (or base stations) and repeaters in the network. The location of the components affects the performance of the network. The assignment of network parameters, such as power of individual network components, and frequencies assigned to geographical areas, also affects the performance of the network. Assigning network parameters is challenging because there is no static solution. Factors such as varying use of the network over time require the finite resources to be distributed differently over time to maximize performance for current users. The "best" network configuration is thus a moving target. Because the experience of the end user is what really matters, performance engineers attempt to collect and analyze data that reflects the end user's experience of the network.

[0002] Traditional approaches to network analysis are very expensive and time consuming. In addition, traditional approaches do not allow the network administrator to react very quickly to network deficiencies. One traditional method of collecting network performance data is drive testing. Drive testing involves a truck full of sophisticated equipment driving through areas covered by a wireless network service provider. A performance engineer on the truck utilizes special equipment to make test calls makes a call to a fixed location. The equipment can send a variety of performance data to the fixed location on demand. During the

call, the fixed location collects performance data from the telephone and the network, such as signal strength, and other measures. Thus, data collected by drive testing provides a fairly precise location for data gathered. The data collected can be associated with the general area the truck is passing through, and thus the mobile data reflects the user's experience in the wireless network. Data collected by drive testing is analyzed to determine adjustments to be made to the network parameters. Changes to network parameters include increasing the power of certain components to reduce the number of dropped calls, reducing the transmitting power to reduce interference, and changing frequency assignments to cell site and sectors.

[0003] Traditional drive testing is very expensive. Also, it can be too expensive to gather enough data to be statistically relevant. Another disadvantage is that gathering data can take so long that the data is not very useful. Obviously, a limited number of trucks are deployed at any time, so that any characterization of the network resulting from the drive testing is incomplete. In addition, it takes time to deploy drive testing trucks, collect data, and make network parameter adjustments. By the time the adjustments are made, the network may require different adjustments. In addition, the results of the adjustment are difficult to determine quickly.

[0004] Another traditional method of collecting network performance data is using data generated by switch statistics software. Switches in the network routinely capture data related to calls. This data reflects performance of the network, but lacks location information. This method is less expensive than drive testing, and is a faster process. Because of the lack of location information, however, only broad, coarse adjustments can be made based on the data analyzed. Because this method does not enable finer adjustments to be made, or even to be detected, this method is not helpful in solving network performance problems that are not easily seen or are geographically limited.

[0005] Efforts have been made to merge the data from the switch and data from drive testing, but this is difficult. Several software vendors sell products that analyze wireless network performance data, display results, and make suggestions regarding network design. The data available still has the limitations discussed above.

[0006] Overall, there is a need for improved performance data collection and analysis in wireless communications networks.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0007] **Figure 1** is a diagram of an embodiment of a real-time network analysis and performance management system.

[0008] **Figure 2** is a diagram of an embodiment of a mobile unit.

[0009] **Figure 3** is a diagram of an embodiment of an alternative location system.

[0010] **Figure 4** is a flow diagram of an embodiment of a real-time network performance analysis and management system.

[0011] **Figure 5** is a block diagram of a data flow between a mobile unit and servers.

[0012] **Figure 6** is a block diagram of a data flow to various servers in one embodiment.

[0013] **Figure 7** is a block diagram of a data flow between a server and a workstation and plotter in one embodiment.

[0014] **Figure 8** is a diagram of one embodiment of a mobile unit architecture and data flow.

[0015] Note: the headings provided herein are for convenience and do not necessarily affect the scope or interpretation of the invention.

#### DETAILED DESCRIPTION

[0016] Embodiments of the invention, described below, use the location of a mobile unit in a wireless network when providing operational performance information. A performance engineer then tunes the system for optimal performance without traditional drive testing. In one embodiment, mobile units are equipped with a location system that calculates the absolute location of the mobile unit. The location system may include Federal Communications Commission ("FCC") mandated enhanced 911 ("E911") technology. The mobile unit is further equipped with a performance monitoring system that responds to requests for performance information from a switch. A performance engineer formulates a query or request for information, which may include selected mobile units,

selected geographical areas and selected time periods. The query further specifies the data requested. The mobile units implicated by the query respond by sending the performance data and location data to the switch. The performance data and location data are linked. The linked performance data and location data are processed and analyzed in real-time to give a very accurate representation of network performance from the subscriber's point of view. Network parameters can be changed on the fly as data is analyzed, and the results of adjustments can be quickly observed.

**[0017]** **Figure 1** is a diagram of an embodiment of a real-time network analysis and performance management system 100. The system 100 includes a mobile switch center 102, also known as switch 102, and servers 110. Servers 110 include location server 110a, database server 110b, and user interface server 110c. The switch 102 and the servers 110 collectively provide data processing and storage. In various embodiments, one server or a number of servers greater than three, could provide all of the data processing and storage capabilities of the switch 102 and the servers 110.

**[0018]** Unless described otherwise herein, the elements depicted in Figure 1 are well known or described in the above cross-referenced provisional patent application. Indeed, much of the detailed description provided herein is explicitly disclosed in the provisional patent application; much of the additional material of aspects of the invention will be recognized by those skilled in the relevant art as being inherent in the detailed description provided in the provisional patent application, or well known to those skilled in the relevant art.

**[0019]** The switch 102 communicates with the cell sites, or PCS sites 104. Sites 104 are also referred to as base stations 104. The base stations 104 are located in different areas within a wireless network and handle communication among mobile units 106, and between the mobile units 106 and other mobile units. The mobile units 106 can be mobile phones, PCS devices, such as personal digital assistants ("PDAs"), or any device that communicates over a wireless network. In the depicted embodiment, the mobile units 106 are Global Positioning System (GPS) enabled. The GPS system uses orbiting GPS satellites, such as GPS satellites 108 to send timing and distance signals directly to a GPS receiver in a GPS enabled device. The precise position of the device is

calculated by software on the receiving device. **Figure 1** shows three GPS satellites, 108a, 108b, and 108c. Three GPS satellites are shown in the figure, but preferably as many as eight are used. The GPS satellites 108 transmit to a GPS receiver in a mobile unit 106 as the subscriber carries it around. The GPS signals are used to calculate a device location that is stored in the mobile unit 106 temporarily.

**[0020]** The user interface server 110c provides a user interface run on the real-time workstation 114. An engineer 118 uses the user interface to create queries for the mobile units 106. The switch 102 receives location data and performance data from the mobile units 106 in response to the queries.

**[0021]** The location server 110a receives and stores information regarding the location of the mobile units 106, such as during emergency 911 calls, to thereby enable the E911 technology noted above. In the depicted embodiment, however, the location server 110a obtains location information for some or all mobile units 106, regardless of whether the mobile unit has placed a 911 call. Use of such location servers is known by those skilled in the relevant art. The location server 110a is connected to a workstation 114 (or another workstation, not shown) to facilitate control over the selection criteria of location and call data, or network performance, records. Various selection scenarios can be used. For example, a group of random mobile identification numbers ("MINs") or electronic serial numbers ("ESNs") can be selected. Criteria such as specific base stations, sectors, control channels, traffic channels, latitude and longitude polygons, date, and time criteria can be used to select records.

**[0022]** To be able to manage this large workload, the location server 110a accesses the call data records as quickly as possible without providing a load on the switch 102 itself. The location server 110b is attached to the switch through a dual-port arrangement to a data storage device in the switch 102.

**[0023]** Location and call data records are forwarded for long term storage to the database server 110b. The database server 110b is also connected to the user interface server 110c, which facilitates analysis and presentation of the data to the engineer 118. Location data and network performance data are optionally shown on the real-time workstation 114 or printed by a plotter 116 or other printer.

Depending on the capacity of the user interface server 110c, more than one real-time workstation 114 and plotter 116 are supported.

**[0024]** The performance engineer 118 analyzes the location data and network performance data from the system, and decides what system parameter changes, or adjustments, to make. These adjustments are accomplished with the mobile switch center ("MSC") workstation 112, which forwards the adjustments to the switch. These adjustments affect the performance of the network. As continued or new observations are selected, the new data is collected by the real-time system and displayed to the performance engineer 118. The cycle of data collection, data analysis, and system adjustment continues to fine-tune the system 100 further.

**[0025]** In other embodiments, other location systems and methods are used. In one embodiment, existing E911 technology is used to obtain location data. E911 technology includes hardware and software in mobile units, network components or both. Recently, the FCC formulated E911 requirements, which are an enhancement to "basic" wireless 911 emergency services. The FCC previously mandated wireless 911 requirements to improve the quality and reliability of 911 emergency services for wireless phone users. The basic 911 rules require wireless carriers to transmit all 911 call to a public safety answering point ("PSAP") without regard to validation procedures intended to identify and intercept calls from non-subscribers. According to phase II E911 requirements, wireless carriers are required to provide automatic location identification ("ALI"). ALI is implemented with, e.g., ALI capable handsets. There are various methods for obtaining location identification, as further discussed below.

**[0026]** **Figure 2** is a diagram of a mobile unit 106. The mobile unit 106 includes an antenna 208, a mobile unit operating system 204, a location system 206, and a performance monitoring system 208. The mobile unit operating system 204 includes hardware and software required to conventionally operate a mobile communications device. The location system 206 includes hardware and software to derive an absolute location of the mobile unit 106, such as a GPS receiver and GPS software. The performance monitoring system 208 includes hardware and software to monitor and store various network performance characteristic measurements (such as signal to noise ratio, bit error rate, and other performance



metrics known to those skilled in the art). The organization and separation of systems by function, as shown in the mobile unit 106, can be varied in other embodiments. For example, other embodiments could have the various hardware and software functions all combined in one system, or divided in a different way.

[0027] **Figure 3** is a diagram illustrating an embodiment using a different location system from that of **Figure 1**. The embodiment of **Figure 3** includes a GPS receiver at each base station 304 of a wireless network. According to well-known methods, the GPS signals to multiple base stations 304 are used to determine the distance of the mobile unit 306 from three or more base stations 304. The mobile unit 306 does not include a GPS receiver, but does include software to send appropriate signals to the base stations 304. The methods include measuring the angle of arrival of the mobile unit 304's signal, and measuring the time difference of arrival ("TDOA") to the base stations 304. Calculated location information is sent as required to the switch 302.

[0028] Another example of determining location (not shown) is a "fingerprint method". Because a mobile unit has one current serving base station and several potential serving base stations, the signal strengths from these sources forms a unique multidimensional array of signal strength values. Each array element corresponds to a specific geographical location and can be encoded with a location. Moving the mobile unit changes the array value. The array value translates to a specific location.

[0029] Other known methods of determining the location of the mobile unit are possible. In any embodiment, regardless of the method used to determine location, the current base station sends the location data to the switch. The same location data is also captured with the call data records in the switch that are used for subscriber billing.

[0030] **Figure 4** is a flow diagram illustrating the operation of an embodiment of a real-time network performance analysis and management system. At 402, a performance engineer sets performance monitoring criteria through a graphical user interface ("GUI"). The performance monitoring criteria include two sets of criteria. One set of criteria, the "who criteria", describe which mobile units are queried. The other set of criteria, the "what criteria", describe what performance data is captured. The who criteria include: specific base stations; specific sectors;

specific control channels; specific traffic channels; specific latitude and longitude polygons; specific dates or times; random groups of mobile units as identified by phone number; and any other criteria associated with a communication over the wireless network involving a mobile unit. The what criteria include: signal strength; dropped calls; bit error rate ("BER"); and any other conventional performance criteria or metric. At 404, any mobile units implicated by the criteria are queried using the criteria.

[0031] At 406, the mobile unit transmits the requested performance data (also known as call data), as well as location data to the switch. The location data describes the location of the mobile unit when the call data was collected. At 408, the location data records and call data records are linked so they can be associated on retrieval. The location data records and call data records are routed to a server for storage at 410.

[0032] The stored records are accessed for analysis at 412. The stored location data records and call data records are accessed in several ways, as specified by a performance engineer. For example, records are accessible by query. That is, every record resulting from a particular query is retrieved. Alternatively, records are accessible by one of the "who criteria" or one of the "what criteria". Because the location data records and call records are linked, the appropriate location will be associated with performance data no matter how the records are retrieved.

[0033] At 414, reports are created as specified by a performance engineer using specific software. The reports may be graphical or they may be text. For example, a graphical report displays the call data as a function of location and time. The location is a location of the mobile unit with a resolution required by enhanced 911. After viewing the reports, the performance engineer may manually adjust network parameters. Alternatively, a software program takes the report as input and automatically adjusts network parameters according to predetermined instructions. The predetermined instructions specify, for example, permissible ranges of certain network performance measures. The process can be repeated starting with setting network monitoring criteria at 402. The affects of adjustments can be easily and quickly observed by querying mobile units again.

[0034] **Figure 5** through **Figure 8** are block diagrams illustrating embodiments of data flows. **Figure 5** illustrates an embodiment of a data flow between a mobile unit and servers. As shown in **Figure 5**, the location server 514 simply reads and copies the location data and the associated call data records 502 according to selection criteria. For privacy, the mobile information number (MIN) and the electronic serial number (ESN) contained in the call data records are discarded or simply not copied to the location server 514. The MIN and the ESN are identifiers associated with a mobile mobile unit. Captured data includes, for example, time, location, serving base station, control channel, traffic channel, uplink signal strength, uplink bit error rate, handoff data, etc.

[0035] The switch 503 includes conventional mobile switch 506 capability and E911 technology 504. In one embodiment, the E911 technology 504 captures the location data, and the mobile switch 506 captures the call data. The E911 technology 504 creates record links 510 between call data records 512 and location data records 508. The location server 514 captures the location data records 508, the record links 510, and the call data records 512.

[0036] **Figure 6** illustrates an embodiment of data processing flow to various other servers. The location server 514 supplies real-time data records 604. Real-time data records 604 are linked location data records and call data records. The real-time data records are captured by a database server 606, which supplies them to a user interface server 610.

[0037] **Figure 7** illustrates how a workstation 704 and a plotter 706 communicate with the user interface server 610 in an embodiment.

[0038] **Figure 8** is a diagram of one embodiment of a mobile unit architecture and data flow. The data path shown is bi-directional. Each mobile unit registers with the network using its voice MIN-ESN identity, data Internet protocol ("IP") address identity, or some other electronic address. The mobile unit can be enabled or disabled for real-time data collection using this registration mechanism. Selected phones or random phones can be queried for their current status and location. For example, mobile units in a given sector are queried on demand to make performance measurements as needed.

[0039] The mobile unit 802 includes operating system software 804 and performance system software 808. The operating software 804 supplies

performance data 806, which is formatted by the performance software 808 and sent as a general packet radio service ("GPRS") packet 810 to the wireless network 812. The packet is sent over the GPRS uplink to a location server, periodically through a switch, in the same manner as any other typical GPRS message. Typical messages include registration, paging, control channel, traffic channel, downlink signal strength, neighbor list and signal strength, bit error, time slot, phone mode, and handoff data. The data IP address routes the message to the location server. The location server and the other servers form a private local area network (LAN). In one embodiment, each of these servers uses a high-speed gigabit Ethernet connection with transmission control protocol over Internet protocol ("TCP/IP"). Therefore, the mobile unit uses its GPRS data mode capability (which includes Ethernet-like addressing) to send datagrams containing performance data back to the location server.

**[0040]** Unless the context clearly requires otherwise, throughout the description and the claims, the words "comprise," "comprising," and the like are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense; that is to say, in a sense of "including, but not limited to." Words using the singular or plural number also include the plural or singular number respectively. Additionally, the words "herein," "hereunder," "above", "below," and words of similar import, when used in this application, shall refer to this application as a whole and not to any particular portions of this application.

**[0041]** The above detailed descriptions of embodiments of the invention are not intended to be exhaustive or to limit the invention to the precise form disclosed above. While specific embodiments of, and examples for, the invention are described above for illustrative purposes, various equivalent modifications are possible within the scope of the invention, as those skilled in the relevant art will recognize. For example, while steps are presented in a given order, alternative embodiments may perform routines having steps in a different order. The teachings of the invention provided herein can be applied to other systems, not necessarily the wireless communication system described herein. The various embodiments described herein can be combined to provide further embodiments. These and other changes can be made to the invention in light of the detailed description.

[0042] Any references and U.S. patents and applications listed above are incorporated herein by reference. Aspects of the invention can be modified, if necessary, to employ the systems, functions and concepts of any patents and applications described above to provide yet further embodiments of the invention.

[0043] These and other changes can be made to the invention in light of the above detailed description. In general, the terms used in the following claims should not be construed to limit the invention to the specific embodiments disclosed in the specification, unless the above detailed description explicitly defines such terms. Accordingly, the actual scope of the invention encompasses the disclosed embodiments and all equivalent ways of practicing or implementing the invention under the claims.

[0044] While certain aspects of the invention are presented below in certain claim forms, the inventors contemplate the various aspects of the invention in any number of claim forms. For example, while only one aspect of the invention is recited as embodied in a computer-readable medium, other aspects may likewise be embodied in a computer-readable medium. Accordingly, the inventors reserve the right to add additional claims after filing the application to pursue such additional claim forms for other aspects of the invention.

CLAIMS

I claim:

- [c1] 1. A method for analyzing performance of a communications network, comprising:
- receiving predetermined data collection criteria, wherein the predetermined data collection criteria designate particular call quality data to be captured from particular mobile units during a particular time period;
  - querying the designated mobile units during the designated time period;
  - receiving call quality data and location data with respect to the mobile unit;
  - processing the call data and location data, including creating a link between the call data and the location data; and
  - transmitting the call data, the location data, and the link to a location server.
- [c2] 2. The method of claim 1, wherein the call data includes:
- time data;
  - serving base station data;
  - control channel data;
  - traffic channel data;
  - signal strength data;
  - bit error rate data; and
  - handoff data.
- [c3] 3. The method of claim 1, wherein the location data includes a location of the mobile unit as determined using global positioning system equipment.
- [c4] 4. The method of claim 1, wherein the location data includes a description of a location of the mobile unit that is compliant with the requirements of enhanced 911 ("E911") services.

- [c5] 5. The method of claim 1, wherein the location data includes a description of a location of the mobile unit as calculated using a time difference of arrival ("TDOA") method.
- [c6] 6. A mobile unit for use in a wireless communications network, comprising:  
an operating system, including hardware and software that performs communications functions;  
call quality data components to determine at least one call quality metric, and  
a location system, comprising hardware and software that determine a location of the mobile unit in compliance with enhanced 911 ("E911") requirements, wherein the location system,  
receives a query from a switch, wherein the query includes a request for call data and location data, wherein the location data comprises a location of the mobile unit in compliance with E911 requirements; and  
transmits the location data and the call quality metric to the switch in response to the request.
- [c7] 7. The mobile unit of claim 6, wherein the location system includes global positioning system equipment.
- [c8] 8. The mobile unit of claim 6, further comprising a performance monitoring system that monitors and stores multiple network performance characteristic measurements.
- [c9] 9. A method for analyzing a wireless communications network in real-time, comprising:  
receiving performance monitoring criteria;  
using the performance monitoring criteria to query at least one mobile unit in the wireless communications network;

receiving at least one response to the query, including call data and location data;  
creating a link between the call data and the location data;  
storing the call data, the location data, and the link in a server;  
accessing the server to retrieve the call data, the location data, and the links;  
using the call data, the location data and the links to create at least one performance report, including a graphical report that displays the call data as a function of location and time, wherein the location is a location of a mobile unit with a resolution required by enhanced 911 ("E911") services, and the time is a time at which the call data was created and at which the mobile unit was in the location.

[c10] 10. The method of claim 9, further comprising automatically adjusting parameters of the wireless communications network based on the at least one performance report and predetermined performance guidelines.

[c11] 11. The method of claim 10, wherein the parameters include power settings of network components, and frequency assignments.

[c12] 12. A wireless communications system, comprising:  
at least one mobile unit, wherein the mobile unit includes a location system that creates location data describing a location of the mobile unit;  
at least one switch in communication with the at least one mobile unit;  
at least one server in communication with the at least one switch, wherein the at least one switch receives network performance data and location data from the at least one mobile unit in response to a request, and wherein the network performance data characterizes network performance from the at least one mobile unit's point of view at the location data during a period of time.

[c13] 13. The wireless communications system of claim 12, wherein the at least one server comprises a user interface server that executes a graphical user



interface ("GUI"), wherein the request is formulated using the GUI to specify particular network performance data to be captured from specific mobile units during a specific period of time.

[c14] 14. The wireless communications system of claim 12, wherein the network performance data includes:

- time data;
- serving base station data;
- control channel data;
- traffic channel data;
- signal strength data;
- bit error rate data; and
- handoff data.

[c15] 15. The wireless communications system of claim 12, wherein the GUI is further used to request performance reports, including accessing the server for specified network performance data and location data, wherein the performance reports include graphical reports that indicate network performance as a function of time and mobile unit location.

[c16] 16. The wireless communications system of claim 12, wherein at least one server further creates a link between network performance data and location data, wherein the location data described a location of a mobile unit from which the network performance data was captured.

[c17] 17. The wireless communications system of claim 13, wherein the request includes criteria that describe which mobile units are queried, and criteria that describe what network performance data is captured.

[c18] 18. The wireless communications system of claim 17, wherein the criteria that describe which mobile units are queried include: specific base stations; specific sectors; specific control channels; specific traffic channels;

specific latitude and longitude polygons; specific dates or times; and random groups of mobile units as identified by an identifier.

[c19] 19. The wireless communications system of claim 17, wherein the criteria that describe what network performance data is captured include: signal strength; path loss; dropped calls; and bit error rate ("BER").

[c20] 20. The wireless communications system of claim 15, wherein the request includes criteria that describe which mobile units were queried, and criteria that describe what network performance data was captured.

[c21] 21. The wireless communications system of claim 20, wherein the criteria that describe which mobile units were queried include: specific base stations; specific sectors; specific control channels; specific traffic channels; specific latitude and longitude polygons; specific dates or times; and random groups of mobile units as identified by phone number (MIN) or electronic serial number (EIN).

[c22] 22. The wireless communications system of claim 20, wherein the criteria that describe what network performance data was captured include: signal strength; dropped calls; and bit error rate ("BER").

[c23] 23. A wireless communications system, comprising:  
a mobile unit, wherein the mobile unit includes,  
    a performance monitoring means that records multiple  
        network performance characteristics; and  
    a location means that creates location data describing a  
        location of the mobile unit with a resolution required by  
        enhanced 911 ("E911") services; and  
a data processing means in communication with the mobile unit,  
    comprising, means for using the network performance characteristics  
    and the location data to create at least one performance report,  
    including a graphical report that displays the call data as a function

of location and time, wherein the location is the location of the mobile unit at the time the network performance characteristics were recorded.

[c24] 24. The wireless communications system of claim 23, wherein the data processing means further comprises:

means for receiving performance monitoring criteria;

means for using the performance monitoring criteria to query the mobile unit; and


means for receiving a response to the query, wherein the response includes the network performance characteristics and the location data.

[c25] 25. The wireless communications system of claim 23, wherein the data processing means further comprises:

means for creating a link between the network performance characteristics and the location data;

means for storing the network performance characteristics, the location data, and the link in a server; and

means for retrieving the network performance characteristics and the location data in response to a request to create at least one performance report.






FIG. 2




FIG. 3




FIG. 4




FIG. 5






FIG. 6




FIG. 7




FIG. 8

US PAGE BLANK (USPTO)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
12 September 2002 (12.09.2002)

PCT

(10) International Publication Number  
**WO 02/071780 A3**

(51) International Patent Classification<sup>7</sup>: **H04Q 7/34**

(21) International Application Number: PCT/US02/06909

(22) International Filing Date: 4 March 2002 (04.03.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/273,739 6 March 2001 (06.03.2001) US

(71) Applicant (for all designated States except US): **AT & T WIRELESS SERVICES, INC.** [US/US]; 14520 N.E. 87th Street, Redmond, WA 98052 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **ZAPPALA, Charles, S.** [US/US]; 16203 NE 3rd Street, Bellevue, WA 98008 (US).

(74) Agents: **ARNETT, Stephen E.** et al.; Perkins Coie LLP, P.O. Box 1247, Seattle, Wa 98111-1247 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:  
5 June 2003

[Continued on next page]

(54) Title: METHOD AND SYSTEM FOR REAL-TIME NETWORK ANALYSIS AND PERFORMANCE MANAGEMENT OF A MOBILE COMMUNICATIONS NETWORK



(57) Abstract: Method for analyzing the performance of wireless communications network and adjusting parameters in the wireless communications network. In one embodiment, the specific location of a mobile unit is linked with performance data obtained from the mobile unit. In another embodiment, specific mobile units are queried, by, e.g. a network switch, to provide specific performance data. The mobile units respond by sending the performance data and location data to the switch. The performance data and location data are linked. The linked performance data and location data are processed and analyzed to give an accurate representation of network performance from the subscriber's point of view. In one embodiment, E911 technology is used to provide location data.

WO 02/071780 A3



*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 02/06909

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 H04Q7/34

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	EP 1 081 972 A (LUCENT TECHNOLOGIES INC.) 7 March 2001 (2001-03-07) abstract; figures 3A-5 column 2, line 32 -column 4, line 4	1,6,9, 12,23
X	& CA 2 316 441 A (LUCENT TECHNOLOGIES INC.) 28 February 2001 (2001-02-28)	1,6,9, 12,23
Y	EP 0 431 956 A (MOTOROLA, INC.) 12 June 1991 (1991-06-12) abstract; figure 1 column 4, line 46 -column 5, line 11 column 6, line 20 - line 28	1-25
Y	US 6 141 565 A (FEUERSTEIN ET AL.) 31 October 2000 (2000-10-31) abstract; claims 14,17; figures 1-3 column 9, line 23 - line 34	1-25
	-/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\* & \* document member of the same patent family

Date of the actual completion of the international search

2 April 2003

Date of mailing of the international search report

11/04/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Danielidis, S

# INTERNATIONAL SEARCH REPORT

Int. Patent Application No.  
PCT/US 02/06909

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 719 563 A (THOMPSON, JR.) 17 February 1998 (1998-02-17) abstract; claim 1; figure 1 ----	1,6,9, 12,23
Y	EP 1 021 055 A (DETEMOBIL GMBH.) 19 July 2000 (2000-07-19) abstract; figure 1 column 3, line 13 -column 5, line 20 ----	1,6,9, 12,23
Y	DE 199 20 587 A (WALKE ET AL.) 16 November 2000 (2000-11-16) abstract; claims 1,4 column 1, line 65 -column 2, line 44 -----	1,6,9, 12,23



## INTERNATIONAL SEARCH REPORT

Information on patent family members

In: onal Application No

PCT/US 02/06909

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1081972	A	07-03-2001	US 6522888 B1	18-02-2003
			AU 5360200 A	08-03-2001
			BR 0003758 A	03-04-2001
			CA 2316441 A1	28-02-2001
			CN 1286578 A	07-03-2001
			EP 1081972 A2	07-03-2001
			JP 2001136121 A	18-05-2001
EP 431956	A	12-06-1991	US 5023900 A	11-06-1991
			EP 0431956 A2	12-06-1991
			US 5095500 A	10-03-1992
US 6141565	A	31-10-2000	NONE	
US 5719563	A	17-02-1998	NONE	
EP 1021055	A	19-07-2000	DE 19900543 A1	20-07-2000
			EP 1021055 A2	19-07-2000
DE 19920587	A	16-11-2000	DE 19920587 A1	16-11-2000

US PAGE BLANK (USPTO)